



A 33,5 B 75 (mm)

## Link

### Technical specification

Linear led light with built in electronic gear. Housing of powder painted extruded aluminum for optimal cooling. Serial connection possible with easy Plug-in system for a continuous row of light. Link is easy and quick to install.

**Model and colors** Available in black.

**Area of use** Linear led light for indoor applications, suitable for general or decoration lighting. Choose between recessed, suspended or ceiling mounted.

### Technical data

Mains (input) voltage	220-240 V
Total weight	1,2 kg/ 2.2 kg/ 3 kg/ 3.5 kg/ 4 kg
Form of protection	IP 20, class I
Light source	LED
Operating position	Horizontal
Start time	Instant
Driver	Built in
Optics	Opaque diffuser

Art no	Description	Color
307-535-20	L 934mm 830	Black
307-500-20	L 1650mm 830	Black
307-510-20	L 2150mm 830	Black
307-520-20	L 2400mm 830	Black
307-530-20	L 2900mm 830	Black
047-273	Wire suspension kit, 4m	-
047-180-xx	Track clip white for threaded rod/wire	-
307-211-001	Recessed bracket kit	-
307-203-001	Locking device for serial connection	-

Type	Delivered lumen output (lm)	System power (W)	EEI <sup>3</sup>
830 934mm	1800	16,3	A+
840 934mm	1900	16,3	A++
830 1650mm	3100	29	A+
840 1650mm	3300	29	A++
830 2150mm	4000	37,5	A+
840 2150mm	4200	37,5	A++
830 2400mm	4500	42	A+
840 2400mm	4700	42	A++
830 2900mm	5400	50	A+
840 2900mm	5600	50	A++

### Note

Wire suspensions kit or recessed bracket kit is ordered separate.

Final shipping destination may require minor modifications of components as well as article numbers, be sure to state the country in which the fixtures will be used.