




Flood 500		Flood 750		Flood 1000	
98°/91°		98°/91°		99°/92°	
m	ø	m	ø	m	ø
1.0	2.05	1.0	2.04	1.0	2.06
2.0	4.10	2.0	4.07	2.0	4.11
3.0	6.15	3.0	6.11	3.0	6.17



## Vector HD 500/750/1000mm

### Technical specification

LED linear light with separate electronic gear. Housing of extruded aluminum for optimal cooling and low weight. NL Power electronic gear for optimal lamp life, light flow and colour performance. High performance energy efficient LEDs. Possible to connect up to 8m Vector LED light with same electronic gear.

**Model and colors** Available with diffuse cover and in different lengths.

**Area of use** Light for indoor back lighting, shelf lighting and other applications.

### Technical data

Mains (input) voltage	220-240 V
LED driver output	Constant voltage 28V, Max 60W
Total weight	0,41kg/m
Form of protection	IP 20, class III
Color temperature	3000/3500/4000 K
Color rendering index (CRI)	80+
Light source	LED
Operating position	Universal
Control gear	Electronic
Start time	Instant
Driver	Separate
Safety glass	Included
Beam spreads	Flood
Design lifetime	L80 B10 50 000h

Art no	Description	Color
231-101-002	Vector HD (L.500 mm), 3500K	Grey
231-102-002	Vector HD (L.750 mm), 3500K	Grey
231-104-002	Vector HD (L.1000 mm), 3500K	Grey
121-508	NLP LED 60E-230V with Halogen free EU cable	Grey
123-72	Cable set, secondary side, 2m	White
123-73	Cable set, secondary side, 4m	White
123-74	Cable set, serial connection, 150mm	White
123-75	Cable set, serial connection, 600mm	White
121-46	Splitter, 6 outlets	Black
123-78-10	Mounting clip bracket	White
123-190-10	Tilt bracket 110 degree	White
123-191-10	Lightgap bracket	White
123-192-10	Tilt bracket 132 degree	White
123-54	End Cover (included)	White
950-01-114	Magnetic strip	-

Type	Delivered lumen output (lm)	System power (W)	EEI <sup>3</sup>
835	710lm/m	7W/m	

### Note

Special versions can also be produced depending on quantity.

Final shipping destination may require minor modifications of components as well as article numbers, be sure to state the country in which the fixtures will be used.