



Spot		Medium		Flood	
17°		23°		38°	
m	∅	m	∅	m	∅
1.0	0.30	1.0	0.41	1.0	0.70
2.0	0.60	2.0	0.83	2.0	1.39
3.0	0.91	3.0	1.24	3.0	2.09

Opal COB 3000

Technical specification

LED Track light with incorporated electronic gear and Chip on board.

Improved color rendering index +90. High quality lenses with three different beam spreads.

Lamp housing of die-cast aluminium for optimal cooling, long lifetime and low weight.

Model and colors Available in white, black and grey.

Accessories Filters

Area of use Track light for indoor applications.

Technical data

Mains (input) voltage	220-240 V
Total weight	1,2 kg
Form of protection	IP 20, class I
Color temperature	3 000 K
Color rendering index (CRI)	90
Light source	LED
Operating position	360°/90°
Start time	Instant
Driver	Electronic, built in
Optics	PMMA lens
Beam spreads	Spot, Medium, Flood

Art no	Description	Color
237-504-10	Spot	White
237-504-20	Spot	Black
237-504-30	Spot	Grey
237-505-10	Medium	White
237-505-20	Medium	Black
237-505-30	Medium	Grey
237-506-10	Flood	White
237-506-20	Flood	Black
237-506-30	Flood	Grey
237-315-001	Anti dazzle shade	Black
237-204-001-10	Flaps kit	White
237-204-001-20	Flaps kit	Black
237-204-001-30	Flaps kit	Grey

Type	Delivered lumen output (lm)	System power (W)	EEI ³
830	2800	27	A+
930	2650	30	A
840	2700	24	A++
940	2650	27	A

Note

Product available in other Kelvin temperatures by request. Final shipping destination may require minor modifications of components as well as article numbers, be sure to state the country in which the fixtures will be used.