




Spot		Medium		Flood	
16°		28°		40°	
m	ø	m	ø	m	ø
1.0	0.28	1.0	0.50	1.0	0.73
2.0	0.56	2.0	1.00	2.0	1.46
3.0	0.83	3.0	1.51	3.0	2.18



A 166 B 172 C 83,5 D 49 (mm)

Revoc mini 2500

Technical specification

Track light with incorporated electronic gear and Chip on board. High quality reflectors with three different beam spreads. Lamp housing of die-cast aluminium for optimal cooling, long lifetime and low weight. Black front ring.

Model and colors Available in white, black and grey.

Area of use Track light for indoor applications.

Technical data

Mains (input) voltage	220-240 V
Total weight	0,76 kg
Form of protection	IP 20, class I
Light source	LED
Operating position	360°/90°
Start time	Instant
Driver	Built in
Optics	Metalized aluminum reflector
Beam spreads	Spot, Medium, Flood

Art no	Description	Color
285-590-10	Spot	White
285-590-20	Spot	Black
285-590-30	Spot	Grey
285-591-10	Medium	White
285-591-20	Medium	Black
285-591-30	Medium	Grey
285-592-10	Flood	White
285-592-20	Flood	Black
285-592-30	Flood	Grey

Type	Delivered lumen output (lm)	System power (W)	EEI ³
930	2400	23	A+
940	2370	23	A+
840	2500	19,5	A++

Note

The above article numbers applies to 930.

Product available in other Kelvin temperatures on request. Final shipping destination may require minor modifications of components as well as article numbers, be sure to state the country in which the fixtures will be used.